

# AN300 Series Large Vane CFM/CMM Thermo-Anemometers



Extech's 4" (10cm) Large Vane Thermo-Anemometer series allows for more precise readings on larger size ducts. Each meter simultaneously displays Airflow or Air Velocity and Temperature. Choose models that also measure Air Volume, Humidity & Carbon Dioxide (CO<sub>2</sub>).

### **Applications:**

- HVAC
- Manufacturing
- Engineering
- Appliance Testing
- Research and Design
- and more!



- · Measure Air Velocity and Air Flow
- Built-in thermistor for air temperature
- · Multipoint and timed average calculations
- Min/Max, Data Hold, and Auto power off
- Optional Air Flow Cone Kit (AN300-C):
   8.26" (210mm) round and 13.6" (346mm) square
- · Complete with four AAA batteries and hard case

### Model AN310 Additional Functions:

• Measures Relative Humidity, Wet Bulb and Dew Point

## Model AN320 Additional Functions:

- · Measures Relative Humidity, Wet Bulb and Dew Point
- Carbon Dioxide (CO<sub>2</sub>) measurement

Specifications	AN300	AN310	AN320
m/s	0.2 to 30m/s	0.2 to 30m/s	0.2 to 30m/s
ft/min	40 to 5900ft/min	40 to 5900ft/min	40 to 5900ft/min
Accuracy	±1.5%	±1.5%	±1.5%
CFM/CMM	0 to 99999	0 to 99999	0 to 99999
Temperature	-4 to 140°F (-20 to 60°C)	-4 to 140°F (-20 to 60°C)	-4 to 140°F (-20 to 60°C)
Accuracy	± (0.6°C)	±1.1°F (0.6°C)	±1.1°F (0.6°C)
Humidity	_	0.1 to 99.9%RH	0.1 to 99.9%RH
Accuracy	_	±3%RH	±3%RH
Wet Bulb	_	-4 to 140°F (-20 to 60°C)	-4 to 140°F (-20 to 60°C)
Dew Point	_	23 to 140°F (-5 to 60°C)	23 to 140°F (-5 to 60°C)
CO <sub>2</sub>	_	_	0 to 9999ppm
Dimensions/ Weight	10.6x4.2x2" (269x106x51mm) / 7oz (200g)		
Difficition of the vivolgine	10.0X1.2X2 (200X100X0111111)/	1 02 (2009)	

# Ordering

AN300Large Vane CFM/CMM Thermo-Anemometer			
AN310Large Vane CFM/CMM Anemometer/Psychrometer			
AN320Large Vane CFM/CMM Anemometer /Psychrometer + $CO_2$			
AN300-C Airflow Cone and Funnel Adapters			



AN300-C - Cone/Funnel Adapters
The meter has a cone and square preset.
With this optional kit it would allow HVAC
technicians to be freed from the hassle
of calculating dimensions and allow for
quick and easy air flow measurments for
these common duct sizes.

 $\in$ 

Specifications subject to change without notice. Copyright © 2012-2013 FLIR Systems, Inc. All rights reserved including the right of reproduction in whole or in part in any form.

www.extech.com